

SPANNSCHLOSS MIT GABEL, VERPRESST_TURNBUCKLE WITH FORK, SWAGED


Artikelnummer Part number	a	b	f	g	ø d	ø d1	ø Seil ø rope	Spannweg Adjustment	kN	l1	l2	ø l
870-0200 dwg	M5	190	12	7,5	5	5	2	+26 -43	2,9	6	10	5,5
870-0300 dwg	M6	220	12	7,5	6	5	3	+28 -50	6,6	6	10	5,5
870-0400 dwg	M6	225	12	7,5	7	5	4	+28 -50	11,5	6	10	5,5
870-0401 dwg	M8	248	13	10	8	6	4	+34 -50	11,8	8	10	6,5
870-0500 dwg	M8	254	13	10	8	6	5	+34 -50	18,5	8	10	6,5
870-0600 dwg	M10	283	15	11	10	8	6	+30 -50	26,7	9	12	8,5
870-0800 dwg	M12	368	25	14	13	12	8	+46 -70	31,5	13	20	12,5
870-1000 dwg	M16	490	31	22	18	14	10	+48 -90	69,4	20	23	14,5
870-1200 dwg	M20	580	42	24	20	19	12	+60 -105	93,6	22	32	19,5
870-1600	M24	680	50	30	27	25	16	+90 -120	133	28	46	26

Werkstoff 1.4401 | kN = Bruchkraft_Material AISI 316 | kN = breaking load